



		Must Be Defined										Options			
		V	2	-											
<u>Down Cable Connection</u>															
7-Pin Amphenol Connector	07														
Internal Connecting Terminal Block	NT														
<u>Supply Voltage</u>															
120 VAC	1														
<u>SCADA Communications</u>															
None	0														
Fiber with ST Connectors	F														
Serial with DB-9 Connector	S														
(Phoenix Conn) Serial Direct Hardwired	D														
(Define if using PoE) Ethernet	E														
<u>Temperature Sensor</u>															
None	0														
Temp	T														
<u>Trip Operation Type</u>															
AC Trip	A														
DC Trip	D														
AC and DC Trip	B														
<u>Current Sensing</u>															
None	0														
(0-10V) LPCS	L														
CT	C														
<u>Cap Bank Wye Neutral Sensing</u>															
None	0														
CT	C														
(120V NOM Secondary) PT	P														
<u>Enclosure</u>															
12x14 Carlon w/ Meter Base	0														
(NMK12V) 12x14 Carlon w/ Carlon Brackets	1														
(VBK01) 12x14 Carlon w/ Aluminum Brackets	2														
<u>Compatible with:</u> DC Trip															
Cooper ECS															
Joslyn VSV	Type 1														
ABB PSx5															
Cooper VCS-1S															
Maysteel UltraVac	Type 2														
<u>Battery Backup</u>															
None	0														
(12V DC) Battery & Charger	1														
<u>Options - Not Necessarily Used</u>															
(Dash)	-														
<u>Radio Part Number</u>															
Freewave FGR2-PE-U	R1														
Freewave FGR09CSU	R2														
GE MDS SDx	R3														
(User Specified Radio)	R0														
<u>Isolation Power Supply</u>															
12 VDC	E1														
(Radio or PoE) 24 VDC	E2														
48 VDC	E4														
IEEE 802.3af	E0														